



MAC SEMI-AUTO BRUSHING BLOCKING STATION

The **MAC SEMI-AUTO BRUSHING BLOCKING STATION** is used to remove excess paste from the bottom and/or sides of the pasted grid stacks. The machine requires one operator to block/square the stack, then place the stack into the clamp area.

The operator presses the two start buttons which activates the clamp and starts the brushes rotating. The machine passes the side(s) of the stack over rotating brushes to remove excess paste and to remove sharp edges from the foot area that may be left after parting. The machine is well ventilated to minimize lead in air. The machine comes in both right and left hand configurations to allow use on opposite sides of a line.

The MAC Semi-Auto Brushing/Blocking Station is a free-standing unit. A 6-inch diameter exhaust collar is provided; 900 CFM exhaust hook-up is required. The unit includes a 2 hp motor, and a collection drawer to collect

paste brushed from the panel edges. The machine will not operate when a plate stack is not present.

Your choice of either metric or English standard fasteners. The equipment will be made

to your electrical requirements.

Optional motorized table height adjustment.



Helping to make the best batteries...yours.

MAC Engineering and Equipment Company, Inc.

2775 Meadowbrook Road, Benton Harbor, Michigan 49022, U.S.A.

Telephone: (269) 925-3295 or 1-800-756-8608 Fax: (269) 925-3305

e-mail: maceng@mac-eng.com

For a preview of our equipment visit: www.mac-eng.com